



UCOCUT-OD

GM-192

Cutting Oil

Product

UCOCUT-OD is cutting oil. For tapping, drilling, reaming, threading, finishing.

Composition

UCOCUT-OD is Petroleum based water-soluble Oil & Non-Flammable solvent.

Description

UCOCUT-OD helps to reduce the effects of friction. It helps to carry away the heat in machine operations. Excessive heat leads to damage of microstructure of metals. UCOCUT-OD makes easy working at metal and helps to improve quality.

Technical Data

FormLiquid
ColourPale Yellow

Advantages

- Ready to use, just add water. (Composition UCOCUT-OD : Water 1:5)
- Reduces costs
- Prevents galling
- Prevents tool seizure
- Non-Flammable
- Non-Explosive
- Non-Toxic
- Assures finer finish
- Featuring VPG for Maximum Vapor Phase Protection

Purpose

- To get ultra-finish precise tolerance
- To increase production
- To increase tap life

Where to use

- For tapping, drilling, reaming, threading, cutting and finishing work.
- For all Metals

Method of use

Ensure continuous flow of the mixer to ensure at the metal work in appropriate dosage/quantity.

Packing

500 ml & 1 Litre Bottles

Storage

- UCOCUT-OD has a shelf life of 12 months from the date of manufacturing, if stored as per manufacturer's instructions & in manufacturer's original unopened packing.
- Keep away from direct sunlight and store in dry & shade.
- Protect from freezing and moisture.

Handling Precaution

- UCOCUT-OD is an industrial chemical; required handling precautions should be followed.
- UCOCUT-OD is non-flammable and doesn't contain any flammable ingredient.
- UCOCUT-OD is non-hazardous, however prolonged breathing of vapor should be avoided. Use of facemask is recommended.
- Prolonged contact with skin should be avoided. Use rubber gloves and boots, when working overhead, goggles should be worn.
- Contact with eye should be avoided. If in contact with eye, wash with water and take medical advice immediately. If swallowed, take medical advice immediately.

Important Note:

All products should be used in accordance with manufacturer's instructions. Every effort is made to ensure that the information is reliable, however we do not accept any responsibility for any work carried out with our material(s) as we have no control over the method(s) used for application, site conditions, weather conditions, etc.

INNOVATIVE
MARKETING

Works:

Plot No. 16, GIDC Industrial Estate, Pardi – 396125, Dist. Valsad, GJ, IND
+91 99250 35219 | info@innovativemarketing.in | www.innovativemarketing.in

Marketed by:



UCLID TECHNOLOGY LTD.
(CONSTRUCTION CHEMICAL DIVISION)

www.uclidtechnology.com